



**Model: BT-1250-MS**

Description:	Bias Tee
Operating Frequency:	50 -1250 MHz
Insertion Loss:	0.2dB Max
Isolation DC to RF:	30dB Min, (40dB Min above 80MHz)
VSWR:	1.2:1 Max
RF Power:	50W CW/AVG
Bias Voltage:	100 Volts Max
Bias Current:	750 mA Max
Bias DC Resistance:	0.2 Ohms
Bias Frequency Bandwidth (Fc @ 3dB):	DC-5MHz
RF Connector:	SMA (female)
RF+DC Connector:	SMA (female)
Bias Connector:	Solder Pin
Impedance:	50 Ohms Nominal
Quality:	Best-Commercial-Grade

**Environmental Ratings:**

Temperature:	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

**Available Options:**

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **RF & RF+DC Connectors**

- B1** [RF port with SMA(M) connector] <> Model: BT-1250-MS-B1
- B2** [RF+DC port with SMA(M) connector] <> Model: BT-1250-MS-B2
- B3** [RF & RF+DC ports with SMA(M) connector] <> Model: BT-1250-MS-B3

**Outline**

