



**Model: BT-H060-LS**

Description:.....	Bias Tee
Operating Frequency:.....	200 KHz – 60 MHz
Insertion Loss:.....	0.15 dB Max
Isolation DC to RF:.....	40dB Min
VSWR:.....	1.2:1 Max
Bias Voltage:.....	50 Volts Max
Bias Current.....	500 mA
..... 0.01dB Compression....	850 mA
..... 0.10dB Compression....	DC-3 KHz
Bias Frequency Bandwidth.....	50W CW/AVG
Power Handling:.....	1 Ohm
Bias DC Resistance:.....	SMA (female)
RF Connector:.....	SMA (female)
RF+DC Connector:.....	Solder Pin
Bias Connector:.....	50 Ohms Nominal
Impedance:.....	Best-Commercial-Grade
Quality:.....	

**Environmental Ratings:**

Temperature:.....	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:.....	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:.....	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:.....	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:.....	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

**Available Options:**

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **RF & RF+DC Connectors**

- B1 [RF port with SMA(M) connector]
- B2 [RF+DC port with SMA(M) connector]
- B3 [RF & RF+DC ports with SMA(M) connector]

■ **Bias Connector**

- C1 [Bias with 50Ω SMC(Jack/Male)]
- C2 [Bias with 50Ω SMB(Jack/Male)]

**Outline**

