



Model: BT-H150-LS

Description:.....	Bias Tee
Operating Frequency:.....	1 – 150 MHz
Insertion Loss:	0.2 dB Max
Isolation DC to RF:	40dB Min
VSWR:	1.3:1 Max
Bias Voltage:.....	50 Volts Max
Bias Current.....	500 mA
..... 0.01dB Compression....	850 mA
..... 0.10dB Compression....	DC-5 KHz
Bias Frequency Bandwidth.....	50W CW/AVG
Power Handling:	0,7 Ohm
Bias DC Resistance:.....	SMA (female)
RF Connector:	SMA (female)
RF+DC Connector:.....	Solder Pin
Bias Connector:	50 Ohms Nominal
Impedance:	Best-Commercial-Grade
Quality:.....	

Environmental Ratings:

Temperature:.....	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **RF & RF+DC Connectors**

- B1 [RF port with SMA(M) connector]
- B2 [RF+DC port with SMA(M) connector]
- B3 [RF & RF+DC ports with SMA(M) connector]

■ **Bias Connector**

- C1 [Bias with 50Ω SMC(Jack/Male)]
- C2 [Bias with 50Ω SMB(Jack/Male)]

Outline

