




**Model: DC-G000-10S**

Description:..... Directional Coupler  
 Operating Frequency:..... 12.4 – 18 GHz  
 Coupling (reference to input):..... 10 ± 1 dB Nominal  
 Coupling Flatness:..... ± 0.6 dB Max  
 Insertion Loss (including coupled power):..... 1.4 dB Max  
 Directivity: ..... 12 dB Min  
 VSWR: ..... Line ..... 1.45:1 Max  
 ..... Couple ..... 1.55:1 Max  
 Power Handling: ..... Incident @ Input ..... 30W Cw/Avg Max  
 ..... Incident @ Output ..... 5W Cw/Avg Max  
 Connectors: ..... SMA (f)  
 Impedance:..... 50 Ω Nominal  
 Quality:..... Best-Commercial-Grade

**Environmental Ratings:**

Temperature:..... {Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}  
 Humidity: ..... MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)  
 Shock: ..... MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)  
 Vibration: ..... MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)  
 Altitude: ..... MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)  
 Temp. Shock: ..... MIL-STD-202F, Method 107D, Cond. A (5 cycles)

**Outline**  
 ("A" = 1.250" [31.8 mm])



Weight	Tolerances
0.75 oz [21.3g]	± 0.015" [ ± 0.38 mm ]