Universal Microwave Components Corp.
5702-D General Washington Drive Alexandria, VA 22312 <> Web: www.umcc111.com
E-mail: sales@umcc111.com <> Tel: (703) 642-6332 <> Fax: (703) 642-2568

Model: DC-J000-10S

Description:		Directional Coupler
Operating Frequency:		0.5 – 2 GHz
Coupling (reference to input):		10 ± 1 dB Nominal
Coupling Flatness:		± 0.5 dB Max
Insertion Loss (including coupled power):		0.8 dB Max
Directivity:		20 dB Min
VSWR:	Line	1.2:1 Max
	Couple	1.2:1 Max
Power Handling:	Incident @ Input	50W Cw/Avg Max
	Incident @ Output	10W Cw/Avg Max
Connectors:		SMA (f)
Impedance:		50 Ω Nominal
Quality:		Best-Commercial-Grade

Environmental Ratings:

Temperature:	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline
("A" = 5.250" [133.4mm])



Weight	Tolerances
2.7 oz [76.5 g]	± 0.015" [± 0.38 mm]

UMCC