Universal Microwave Components Corp.
5702-D General Washington Drive Alexandria, VA 22312 <> Web: www.umcc111.com
E-mail: sales@umcc111.com <> Tel: (703) 642-6332 <> Fax: (703) 642-2568

Model: DC-Y000-30S

Description:		Directional Coupler
Operating Frequency:		5 - 10 GHz
Coupling (reference to input):		30 ± 1 dB Nominal
Coupling Flatness:		± 0.75 dB Max
Insertion Loss (including coupled power):		0.3 dB Max
Directivity:		14 dB Min
VSWR:	Line	1.30:1 Max
	Couple	1.35:1 Max
Power Handling:		50W Cw/Avg, 1KW Peak
Connectors:		SMA (f)
Impedance:		50 Ohms Nominal
Quality:		Best-Commercial-Grade

Environmental Ratings:

Temperature:	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline
("A" = 1.450" [36.8mm])



Weight
1.1 oz [31.2 g]

UMCC