



Model: SW-G270-2S

Description: SP2T, Absorptive, PIN-Switch
Operating Frequency: 0.3 - 20 GHz
Insertion Loss: 2.9dB Max
Isolation:

Table with 2 columns: Frequency Range (0.3 - 10 GHz, 10 - 20 GHz) and Isolation (70 dB Min, 55 dB Min)

VSWR (RF Path "ON" or "OFF"): 1.8:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): 50ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 150ns Max
Phase Balance (Deviation from Median): ±6° max
Operating Power: CW & AVG: +24dBm Max
Peak: 5W @ 1µS PW Max
Control Input Characteristics: TTL / Unit-Load / Floating-High
Control Logic: 2-Controls, Logic "0" = RF Path "ON"
Power Supplies: +5(±0.25) V @ 75mA Max
-12(±0.5) V @ 50mA Max
Connectors (RF): SMA (f), Removable
Connectors (Supplies/Control): Solder Pins
Impedance: 50 Ohms Nominal
Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

Supply Voltages

- A1 [ +5(±0.25)V / -5(±0.25)V ] \*
A2 [ +5(±0.25)V / -15(±0.5)V ]
A3 [ +12(±0.5)V / -12(±0.5)V ]
A4 [ +15(±0.5)V / -15(±0.5)V ]

Control Connectors

- C1 [ SMC(Jack), 50 Ω ]
C2 [ SMB(Jack), 50 Ω ]

RF Connectors

- B1 [ J1 & J2 Ports with SMA(M) ]
B2 [ All SMA (M) ]
B3 [ COM Port with SMA(M) ]

Control Impedance

- D1 [ 50 Ω, Internally Terminated ]

Control Function


- F1 [ Inverse Logic, ("1" = Path "ON") ]
F2 [ Single Toggle Control ("1" for J1 path "ON") ]

\* Recommended for Low Power Consumption <> Additional Switching Delay (On/Off Time)



Model: SW-G270-2S

**Outline**



Weight	Tolerances
0.7 oz [19.8 g]	±0.015" [±0.38mm]