



Model: SR-V01P-8S

Description:..... SP8T, Absorptive, PIN-Switch

Operating Frequency:..... 0.1 – 18 GHz

Insertion Loss:

0.1 – 10 GHz	10 – 18 GHz
4.5 dB Max	5.8 dB Max

Isolation:

0.1 – 10 GHz	10 – 18 GHz
70 dB Min	60 dB Min

VSWR (RF Path “ON” or “OFF”): 2.1:1 Max
 Rise/Fall time (10% to 90% RF, 90% to 10% RF): 35 ns Max
 On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 120 ns Max
 Phase Balance (Deviation from Median): ±14° max
 Operating Power:..... CW&AVG..... +24dBm (+27dbm @ COM Port)
 Peak: 8W @ 1µS PW Max
 Control Input Characteristics: TTL /Unit-Load / Floating-High
 Control Logic:..... 8-Controls, Logic “0” = RF Path “ON”
 Power Supplies:..... +5(±0.25)V @ 260mA Max
 -12(±0.5)V @ 100mA Max
 Connectors (RF): SMA (f), Removable
 Connectors (Supplies/Controls) Solder Pins
 Impedance: 50 Ohms Nominal
 Quality:..... Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
 Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
 Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
 Vibration: MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)
 Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
 Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

- A2 [+5(±0.25)V / -15(±0.5)V]
- A3 [+12(±0.5)V / -12(±0.5)V]
- A4 [+15(±0.5)V / -15(±0.5)V]

■ **RF Connectors**

- B1 [J1 – J8 Ports with SMA(M)]
- B2 [All SMA (M)]
- B3 [COM Port with SMA(M)]


■ **Control Function**

- F1 [Inverse Logic, (“1” = Path “ON”)]
- F2 [3-BCD Controls]



Model: SR-V01P-8S

Outline



Weight	Tolerances
	$\pm 0.015''$ [$\pm 0.38\text{mm}$]