



Model: SW-V070-8S

Description:..... SP8T, Absorptive, PIN-Switch
Operating Frequency:..... 0.1 – 18 GHz
Insertion Loss: 5.0 dB Max
Isolation:

0.1 – 15 GHz	15 –18 GHz
75 dB Min	65 dB Min

VSWR (RF Path “ON” or “OFF”): 2.1:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 50 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF):..... 150 ns Max
Phase Balance (Deviation from Median):..... ±9° max
Operating Power:..... CW&AVG..... +24 dBm Max
..... Peak: 5W @ 1µS PW Max
Control Input Characteristics: Std. TTL / Unit-Load / Floating-High
Control Logic:..... 8-Controls, Logic “0” = RF Path “ON”
Power Supplies:..... +5(±0.25)V @ 260mA Max
..... -12(±0.5)V @ 120mA Max
Connectors (RF):..... SMA (f), Removable
Connectors (Supplies/Controls) Solder Pins
Impedance: 50 Ohms Nominal
Quality:..... Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

- A2 [+5(±0.25)V / -15(±0.5)V]
- A3 [+12(±0.5)V / -12(±0.5)V]
- A4 [+15(±0.5)V / -15(±0.5)V]

■ **RF Connectors**


- B1 [J1 – J8 Ports with SMA(M)]
- B2 [All SMA (M)]
- B3 [COM Port with SMA(M)]

■ **Control Function**

- F1 [Inverse Logic, (“1” = Path “ON”)]



Model: SW-V070-8S



Weight	Tolerances
1.85 oz [52.4g]	±0.015" [±0.38mm]